


LETTER BANNER



For bled edge printing artwork should have 3 mm overfill

File:	Always provide your design as a PDF using the cut line from our technical drawing. Add your own shape and set the cut lines to overprint.
Print colours:	For designs with one, two or more spot colours, always use the Pantone Coated colour profile. Submit full-colour designs in CMYK. For black, use 100% K (0 / 0 / 0 / 100 CMYK).
Resolution:	A resolution of 300 dpi is recommended (minimum 150 dpi), or submit your artwork as a vector file. The higher the resolution, the better the print quality.
Text:	Always convert all text to outlines.
Print marks:	The file must be submitted without print marks.
Text size:	Small text and fine details may fill in during printing.
Readability:	Check the readability by viewing the file at 100% size (do not zoom in).
Safety margin:	Place all important elements, such as text and logos, at least 1 cm away from the cut line.
Bleed:	For designs with bleed, extend backgrounds and images 3 mm beyond the cut line.
Layers:	Place all design elements in a different layer from the cut lines.

Check before submitting:

- ☐ PDF placed within the cut lines
- ☐ No print marks
- ☐ 3 mm bleed included
- ☐ Text converted to outlines
- ☐ Images at a minimum of 300 dpi
- ☐ All important elements at least 1 cm away from the cut line.
- ☐ Design placed on a different layer from the cut lines
- ☐ Print colours set correctly

Use this checklist to verify that the files you are submitting are ready for production.
This helps prevent delays in processing your order.